

Technical Sprays

Lubricating and Multifunctional Oils

Processing

Clean and degrease surfaces prior to application. Shake can well and apply from a distance of approx. 25 cm.

Storage

Pressurized container. Protect from direct sunlight and temperatures above +50°C.

Safety and health

When using WEICON products, the physical, safety-related, toxicological and ecological data and regulations in our EC safety data sheets (www.weicon.com) must be observed.

Available sizes:

11350400 Silicone Spray, 400 ml, colourless, transparent

Silicone Spray



lubricant and release agent

WEICON Silicone Spray is a sliding and release agent as well as a preservative and care product for plastic, rubber and metal. The spray provides a durable separating film and good surface properties and is temperature-resistance up to +250°C (+482°F). Silicone Spray prevents the formation of adhesive residues on presses and guides, prevents products from sticking to conveyor belts, chutes and sliding ways, protects electrical contacts from moisture, preserves rubber, plastic and metal parts, protects rubber parts from becoming brittle, freezing and sticking, and allows sunroof rails, seat tracks and seatbelt to run smoothly.

Technische Daten

Odour	solvent
Colour	colourless, transparent
Specific properties	based on silicone oil
Silicone-free	yes
Temperature resistance	-50°C to +250°C
ISSA Code	53.402.14
Shelf life	24 mon.



The specifications and recommendations given in this technical data sheet must not be seen as guaranteed product characteristics. They are based on our laboratory tests and on practical experience. Since individual application conditions are beyond our knowledge, control and responsibility, this information is provided without any obligation. We do guarantee the continuously high quality of our products. However, own adequate laboratory and practical tests to find out if the product in question meets the requested properties are recommended. A claim cannot be derived from them. The user bears the requested properties are recommended. A claim cannot be derived from them.